



HIGH DENSITY CONNECTION BOX 6U

Installation Environment	Under raised floor with at least 20 cm height (no use of brackets) and at least 23 cm with the use of brackets.
Operation Environment	Indoor non aggressive
Standard	19"
Advantage	<p>Connection point to be used under raised floor. Reach up to 336 ports.</p> <p>Supports:</p> <ul style="list-style-type: none"> • 288 points CAT.5e with Patch Panel 1U 48P or, • 288 points CAT.6 with Patch Panel 1U 48P or, • 144 points Cat.6A with Patch Panel 1U 24P or, • 336 points with optical cassettes for 24F or, • 168 points with optical cassettes for 12F or, • 336 points with optical plates 12 positions or, • 224 points with optical plates 8 positions or, • 168 MPO adapters with 6 positions plates or, • 144 coaxial connections.
Height (mm)	180mm
Width (mm)	580mm (without side tab)
Depth (mm)	580mm (Without side tab)
Color	Gray
Paint Type	Epoxy
Painting thickness (mm)	0.1mm
Thickness sheet (mm)	1mm
Connector Type	Supports all line of metal connectors UTP and optical, including MPO modules.
Number of Positions	Maximum 288 ports as defined in TIA/EIA-942 Telecommunications Infrastructure Standard for Data Center standard.
Main Product Material	Aluminum: Box, cover, frame and cable entry. Carbon steel: external and internal brackets.
Included Accessories	Supplied with installation accessories
Warranty	12 months

RoHS	This product is in accordance with the RoHS European Directive: a directive on the restriction of the use of certain hazardous substances and related to the environmental preservation.
Standard	ANSI/TIA-569-C EIA/ECA-310-E

[Part Numbers](#)