



LGX MODULAR PATCH PANEL

Installation Environment	Indoor
Operation Environment	Non Aggressive
Compatibility	Cabinets 19"
Advantage	<ul style="list-style-type: none"> • Resistant and corrosion-protected product for the conditions specified for indoor use (ANSI/TIA-569); • Displays width of 19" according to requirements of the standard EIA/ECA-310E; • Suitable for LGX cassettes and LGX plates; • Allows the use, at the same time, of optical cables and metallic cables at the same patch panel; • Modularity, the same LGX accessories used on B48 ODF and on the ZDA's can be used on this product; • Compatible with all Furukawa female connectors U/UTP, F modules and modules with optical adapters, if provided the appropriate LGX plate; • Supplied with fixing screws; • Supplied without (unloaded) connectors or adapters LGX.
Height (mm)	44.45mm (1U)
Width (mm)	482.6mm (19")
Depth (mm)	169 mm
Color	Black
Paint Type	Finished in scratchproof high resistant black epoxy
Painting thickness (mm)	0.1 mm
Thickness sheet (mm)	1.2mm
Connector Type	Casette MPO 12/24F, LGX Plates 6/8/12, LGX Plates 6xRJ45
Number of Positions	03 placas LGX
Main Product Material	Carbon Steel / SAE1006 or higher grade

RoHS	This product is in accordance with the RoHS European Directive: a directive on the restriction of the use of certain hazardous substances and related to the environmental preservation.
Standard	ANSI/TIA-569-E EIA/ECA-310-E
Warranty	12 months
Package Type	Box
Quantity per gift box	01 piece
Quantity per box (carton)	01 piece

[Part Numbers](#)