CLOSED HORIZONTAL PLASTIC CABLE MANAGER 1U

Installation Environment	Indoor
Operation Environment	Indoor non aggressive
Compatibility	Cabinets 19"
Advantage	• Made of High-Impact thermoplastic UL 94 V-0; • Resistant and corrosion-protected product for the conditions specified for indoor use by (ANSI/TIA-569); • It features width 19" as the EIA/ECA-310E standard requirements; • Has frontal manufacturer identification with icon; • Has frontal cover that opens upwards and downwards; • Ensures the perfect cable management, respecting the bend radius determined by ANSI/TIA-568; • Supports up to 24 cables U/UTP CAT.5e or CAT.6.
Height (mm)	• Total: 1U • Useful: 22mm
Width (mm)	482mm (19")
Depth (mm)	• Total: 75mm • Useful: 50mm
Color	Black
Paint Type	High impact thermoplastic UL 94 V-0
Main Product Material	High-impact thermoplastic UL 94V0
Maximum Statical Load (N)	CAT.5e - (24 cables) CAT.6 - (24 cables)
Package Type	Cardboard
Quantity per box (carton)	15 pieces
Quantity per gift box	01 piece
Warranty	12 months
RoHS	This product is in accordance with the RoHS European Directive: a directive on the restriction of the use of certain hazardous substances and related to the environmental preservation.
Certifications	UL Listed E173971

FURUKAWA ELECTRIC

This technical document is authored and exclusively owned by Lightera. It is forbidden to reproduce in whole or in part without mentioning its authorship, as well as changing its content or context. All specifications are subject to change without notice.

1/2

| Standard | ANSI/TIA-569-C |
| | EIA/ECA-310-E |

Part Numbers