

SLIMBOX 12 - FIBER INTERNAL ADAPTER MODULE (CEIP 12)

Description	<p>Capable of performing the termination of optical cables using fusion splices, field connectorization or factory terminated cables.</p> <p>Settings:</p> <ul style="list-style-type: none"> • CEIP 12 (splices): up to 12 colored pigtails with SC-APC connectors and without splitter: <ul style="list-style-type: none"> • For the standard model of this configuration, the splice protectors must be acquired separately. • CEIP 12 (splitter): pre-connectorized 1x8 splitter with SC-APC connector.
Application	It is used as a termination point for optical fiber in an indoor environment
Advantage	<ul style="list-style-type: none"> • Allows new cables installation without interference in cables previously installed; • Possibility of pivoting the adapter plate for maintenance without the need to disable any customer; • Internally installed adapters for mechanical protection of optical drop; • System for fixation of optical cables strength members (aramid yarns or FRP) • Specific area for accommodation of fiber and fiber slack; • Separation of the activation area (customers drop optical connectors) and the installation area (pigtails, outputs of splitters and splices); • Colored 900um tight buffered pigtails at ABNT or Telcordia collar pattern.
Installation Environment	Indoor.
Operation Environment	Indoor.
Operation Temperature (°C)	-25 to 75°C
Height (mm)	216
Width (mm)	126
Depth (mm)	70
Weight (kg)	0,45 (basic module)
Color	Gray.
Cable Type	Tight, loose, micromodule, low friction.

Maximum cable Input diameter (mm) 2 cables with 8 mm.

Output cable diameter (mm) 2x1.6 or 3x2.

Fiber Type Singlemode and multimode.

Connector Type SC-APC.

Main Product Material PC+ABS, high resistance thermoplastic.

protection rating IP30.

Impact protection IK05.

Splicing support Minimum: 3x3x60
Maximum: 3.8x6.5x60

Identification Inner identification label for fibers management.

Adapters Quantity 12 (maximum quantity)

*** Check the adapters quantity with Furukawa according to the model chosen.

Splice Trays Quantity 2 (1 for splitter and 1 for pigtails).

Splice Capacity 12 (to dedicated pigtails splice tray).
2 (to dedicated splitter splice tray).

Quantity per box (carton) 16




Quantity per gift box 1

Warranty 12 months

Note According with the disponibility of the region:

1. According with the extended FBS warranty program.

Technical drawing



[Part Numbers](#)