


SLIMBOX 12 - FIBER INTERNAL ADAPTER MODULE (CEIP 12)

Description	<p>Capable of performing the termination of optical cables using fusion splices, field connectorization or factory terminated cables.</p> <p>Settings:</p> <ul style="list-style-type: none"> CEIP 12 (splices): up to 12 colored pigtails with SC-APC connectors and without splitter: <ul style="list-style-type: none"> For the standard model of this configuration, the splice protectors must be acquired separately. CEIP 12 (splitter): pre-connectorized 1x8 splitter with SC-APC connector.
Application	It is used as a termination point for optical fiber in an indoor environment
Advantage	<ul style="list-style-type: none"> Allows new cables installation without interference in cables previously installed; Possibility of pivoting the adapter plate for maintenance without the need to disable any customer; Internally installed adapters for mechanical protection of optical drop; System for fixation of optical cables strength members (aramid yarns or FRP) Specific area for accommodation of fiber and fiber slack; Separation of the activation area (customers drop optical connectors) and the installation area (pigtails, outputs of splitters and splices); Colored 900um tight buffered pigtails at ABNT or Telcordia collar pattern.
Installation Environment	Indoor.
Operation Environment	Indoor.
Operation Temperature (°C)	-25 to 75°C
Height (mm)	216
Width (mm)	126
Depth (mm)	70
Weight (kg)	0,45 (basic module)
Color	Gray.
Cable Type	Tight, loose, micromodule, low friction.
Maximum cable Input diameter (mm)	2 cables with 8 mm.
Output cable diameter (mm)	2x1.6 or 3x2.
Fiber Type	Singlemode and multimode.
Connector Type	SC-APC.

Main Product Material	PC+ABS, high resistance thermoplastic.
protection rating	IP30.
Impact protection	IK05.
Splicing support	Minimum: 3x3x60 Maximum: 3.8x6.5x60
Identification	Inner identification label for fibers management.
Adapters Quantity	12 (maximum quantity) *** Check the adapters quantity with Furukawa according to the model chosen.
Splice Trays Quantity	2 (1 for splitter and 1 for pigtails).
Splice Capacity	12 (to dedicated pigtails splice tray). 2 (to dedicated splitter splice tray).
Quantity per box (carton)	16
Quantity per gift box	1
Warranty	12 months
Note	According with the disponibility of the region: 1. According with the extended FBS warranty program.

Technical drawing



[Part Numbers](#)