



GIGALAN F/UTP 23AWGX4P CAT.6A LSZH-22A EUROCLASS Dca

Description	Shielded data cable GigaLan Category 6A for indoor applications																	
Application	It supports: 10GIGABIT ETHERNET, IEEE 802.3an; GIGABIT ETHERNET, IEEE 802.3z; 100BASE-TX, IEEE 802.3u; 100BASE-T4, IEEE 802.3u; 100vg-AnyLAN, IEEE802.12; ATM-155 (UTP), AF-PHY-OO15.000 and AF-PHY-0018.000; TP-PMD, ANSI X3T9.5; 10BASE-T, IEEE802.3; TOKEN RING, IEEE802.5; 3X-AS400, IBM; POE+ technology (in accordance to IEEE 802.3at and TSB-184).																	
Category	CAT.6A																	
Installation Environment	Internal																	
Operation Environment	Non heavy																	
Compatibility	FCS products																	
Conductor	Solid bare copper																	
Conductor Gauge	23AWG																	
Insulation	High density Polyethylene nominal diameter 1.1 mm																	
Pair	All pairs are twisted in such way to reduce Crosstalk effects. Each conductor is identified according with the following color sequence.																	
Number of Pairs	4																	
Integrated Pair Divider	Yes																	
Core	All pairs are assembled, making the core cable. It has a central element (cross web) made of a thermoplastic material to separate all 4 pairs.																	
Construction	F/UTP																	
Color code	<table><tr><td>Pair</td><td>Conductor "A"</td><td>Conductor "B"</td></tr><tr><td>1</td><td>White</td><td>Blue</td></tr><tr><td>2</td><td>White</td><td>Orange</td></tr><tr><td>3</td><td>White</td><td>Green</td></tr><tr><td>4</td><td>White</td><td>Brown</td></tr></table>			Pair	Conductor "A"	Conductor "B"	1	White	Blue	2	White	Orange	3	White	Green	4	White	Brown
Pair	Conductor "A"	Conductor "B"																
1	White	Blue																
2	White	Orange																
3	White	Green																
4	White	Brown																
Shield	Shielded																	
Drain Wire	26 AWG wire in contact with the foil.																	
Ripcord	With ripcord																	
Sheath	LSZH compound, flame retardant, suitable to meet the cable flame rating class																	
Color	Gray Other colors on request																	

Cable Flammability Rating LSZH: IEC60332-1, IEC60332-3-22A

Nominal Diameter 7.3mm

Operation Temperature -20° up to 60°C

Storage Temperature -20° up to 60°C

Installation Temperature 0°C up to 50°C

Pulling Tension > 400 N

Insulation Resistance 10000 M.km

Maximum Unbalance Resistance 4%

Conductor Max. DC Resistance @ 20 °C 93.8 /km

Maximum Mutual Capacitance @ 1 kHz 56 pF/m

Max. Unbalance Capacitance Pair x Ground @ 1 kHz 3.3 pF/m

Dielectric strength	Between conductors	Between each conductor and shield
	2500 VDC/3s	2500 VDC/2s

Characteristic Impedance 100±15%

Maximum Propagation Delay 545ns/100m

Maximum Delay Skew 45ns/100m

NVP 68%

Transmission Performance

Freq (MHz)	IL (dB/100m)		NEXT (dB)		PSNEXT (dB)		ACRF (dB)	
	TIA/EIA Max.	Typical	TIA/EIA Min.	Typical	TIA/EIA Min.	Typical	TIA/EIA Min.	Typical
1	2.1	1.6	74.3	104.6	72.3	91.4	67.8	100.8
4	3.8	3.2	65.3	93.8	63.3	80.2	55.8	95.6
8	5.3	4.8	60.8	91.3	58.8	78	49.7	89.4
10	5.9	5.3	59.3	95.6	57.3	73.8	47.8	87.4
16	7.5	6.7	56.2	79.9	54.2	72.6	43.7	80.8
20	8.4	7.7	54.8	82.1	52.8	71.8	41.8	77.9
25	9.4	8.7	53.3	85.9	51.3	72.8	39.8	76.6
31.25	10.5	9.6	51.9	75.3	49.9	69.4	37.9	74.6
62.5	15	13.8	47.4	68.6	45.4	60.8	31.9	64
100	19.1	17.6	44.3	66.5	42.3	61	27.8	60.3
200	27.6	25.2	39.8	63.3	37.8	56.2	21.8	57.5
250	31.1	28.4	38.3	59.5	36.3	53.8	19.8	50.5
300	34.3	31.1	37.1	59.2	35.1	51.9	18.3	49.8
400	40.1	36.3	35.3	57.6	33.3	49.6	15.8	49.7
500	45.3	40.7	33.8	54.4	31.8	48.6	13.8	43.2
550	-	41.0	-	42.2	-	40.2	-	36.3
600	-	42.5	-	34.0	-	33.2	-	35.5
700	-	46.3	-	32.0	-	30.0	-	31.6

Freq (MHz)	PSACRF (dB)		RL (dB)		PSANEXT (dB)		PSAACRF (dB)	
	TIA/EIA Min.	Typical	TIA/EIA Min.	Typical	TIA/EIA Min.	Typical	TIA/EIA Min.	Typical
1	64.8	93.8	20	35.4	67	90	67	88
4	52.8	88.4	23	37.2	67	90.8	66.2	87.3
8	46.7	81.8	24.5	42.3	67	92.8	60.1	87
10	44.8	77.7	25	36.9	67	92.4	58.	87.1
16	40.7	71.3	25	40.5	67	91.9	54.1	84.7
20	38.8	69.6	25	39.9	67	85.3	52.2	79.3
25	36.8	67.4	24.3	38.2	67	86.5	50.2	77.8
31.25	34.9	65.8	23.6	39.5	67	86.2	50.2	76.9
62.5	28.8	58.4	21.5	31.3	65.6	85.6	42.3	72.3
100	24.8	53.7	20.1	31.2	62.5	86.6	38.2	68.9
200	18.8	50.8	18	30.2	58	83.6	32.2	60.5
250	16.8	44.8	17.3	26.2	56.5	83.9	30.2	56.9
300	15.3	44.2	16.8	29.5	55.3	81.8	28.7	52.8
400	12.8	42.3	15.9	26.5	53.5	79.7	26.2	46.8
500	10.8	35.4	15.2	21.8	52	76.7	24.2	38.6
550	-	34.6	-	20.4	-	74.0	-	33.0
600	-	34.0	-	17.4	-	72.9	-	30.8
700	-	30.1	-	15.6	-	70.9	-	26.9

Cable Measurements are made at 20 °C in 100 meters cables, pulled out of their packages and released on a non-conductive surface as described in ANSI/TIA-568.2-D. Alien Crosstalk measurement made at 20 °C in seven 100 meters samples (Six around one configuration) according to ANSI/TIA-568.2-D.

Standard	ANSI/TIA-568.2-D ISO/IEC 11801 IEC 61156-5 IEC 60332-1, IEC 60332-3-22A (Flame) IEC 60754-2 (Acidity of smoke) IEC 61034-2 (smoke density) CENELEC/EN 50288-10-1 EN 50173	
Certifications	ETL Verified	3130563
	ETL 4 connections	101795378CRT-001a
	CPR	Dca (s2,d2,a1)
Warranty	12 months	
Marking	FURUKAWA GIGALAN CAT 6A F/UTP 23AWGX4P LSZH 75°C PoE++ EN 50399 Euroclass Dca-s2,d2,a1 - ETL VERIFIED TO TIA-568.2-D CAT 6A YAAMMDDHHmm {1}m Where: YAAMMDDHHmm - Y: Traceability, AA: Year, MM: Month, DD: Day, HH: Hour, mm: minute {1} - Sequential length marking in meters	
Cable Weight	52 kg/km	
Package	305m: plywood reel	

1000m: wooden reel

[Part Numbers](#)